

DEL Plus

3 PHASE ELECTRIC INSTANTANEOUS

Enjoy a high level of convenience.

An efficient electric instantaneous water heater with 3i technology and a wide range of features.

AVAILABLE THROUGH SUNCITY



Comfort and convenience

Improving on the original DEL, the DEL Plus electric instantaneous water heater features a backlit multifunction display, temperature memory, childproofing and ECO mode. The energy and water saving ECO mode can limit the maximum flow rate to help maintain a constant hot water temperature even where inlet temperatures are low.

- Made in Germany
- Maximum hot water output temperature 50 °C, no tempering valve needed
- Save energy and water - 3 stage ECO mode
- Electronically controlled
- Temperature memory function keys
- Temperature limiting function for childproofing (anti-scalding protection)

Need help choosing the right instantaneous hot water system?

CALL 1300 728 122

Technical specifications

Type	DEL 13 Plus	DEL 18 Plus	DEL 27 Plus
Article no.	234470	236741	236742
Rated output (415 V)	14.5 kW	19.4 kW	28 kW
Rated current (415 V)	20.2 A	27 A	38.9 A
Connection	3/PE	3/PE	3/PE
Fuse protection	20 A	32 A	40 A
Electrical installation	As per AS/NZS3000	As per AS/NZS3000	As per AS/NZS3000
Installation requirements	AS/NZS3500.4.2 & local requirements	AS/NZS3500.4.2 & local requirements	AS/NZS3500.4.2 & local requirements
Switch on flow rate	2.5 L/min	2.5 L/min	2.5 L/min
Temperature settings	Off, 20-50 °C	Off, 20-50 °C	Off, 20-50 °C
Water connection	G 1/2 A	G 1/2 A	G 1/2 A
Max. permissible pressure	1000 kPa	1000 kPa	1000 kPa
Max. inlet temp. for reheating	50 °C	50 °C	50 °C
IP rating	IP25	IP25	IP25
Height	466 mm	466 mm	466 mm
Width	225 mm	225 mm	225 mm
Depth	116 mm	116 mm	116 mm
Weight	3.2 kg	3.2 kg	3.2 kg
Colour	White	White	White
Approvals	WaterMark WMKA00301 / AS3498	WaterMark WMKA00301 / AS3498	WaterMark WMKA00301 / AS3498

Temperature rise (415 V)

Flow	DEL 13 Plus	DEL 18 Plus	DEL 27 Plus
6 L/min	+34 °C	+46 °C	-
8 L/min	+26 °C	+34 °C	+46 °C
10 L/min	+21 °C	+27 °C	+39 °C
12 L/min	+17 °C	+23 °C	+33 °C
14 L/min	+15 °C	+19 °C	+28 °C

Seasonal average cold water temperatures

Melbourne: 15 °C

Sydney / Brisbane / Perth / Adelaide: 18 °C

Canberra / Hobart: 14 °C

Townsville / Darwin: 25 °C

Calculating output water temperature

Add the temperature rise values to the incoming cold water temperature to calculate output at the desired flow rate.

Connections: In-wall or bottom entry connection available.

The DEL Plus electric instantaneous 3 phase water heater delivers hot water not exceeding 50 °C in accordance with AS3498. Refer to AS/NZS3500.4, local requirements and installation instructions to determine if additional delivery temperature control is required.

Product specifications reproduced from the supplied STIEBEL ELTRON DEL Plus technical datasheet (Issue 05_24). Features and specifications may change. Images are for reference only. Confirm current equipment features and installation requirements before installation.